

# Outstanding **Productivity** at an exceptional **quality**

## **Product Info**

- 1. TabSpin012 is a practical, compact and reliable laboratory assistant which the highest speed reach 14,500rpm.
- 2. Humanized design, simple and compact appearance, special processing of low noise design create a quiet, comfortable experimental environment for you.



### Tabspin LA1090

#### Features

- Extremely quiet operation
- Easy-to-follow LCD display
- Capacity: 12 x 1.5/2.0ml tubes
- Separate short-spin key
- Low sample heating (only 12°C after 30min, at max.speed)
- Autoclavable rotor (121°C, 20min)
- RMP/RCF setting as required
- Standard rotor made of anodized aluminum
- Timer can be set up to 99min

# **Technical Data**

Model	TabSpin012
Power requirement	100W
Relative centrifugal force (RCF)	14,000 x g
Max.rotational speed	14,500rpm
Timer	20sec~99min
Acceleration time to max. speed	15s
Braking time from max. speed	15s
Dimensions (DxWxH)	270x230x155mm





#### **Product Info**

- 1. TabSpin006 is compact and cost effective, allowing any workstation to be equipped with a "personal" mini centrifuge.
- 2. It is supplied with one rotor suitable for 6-1.5/2.0ml tubes, 6-0.5ml tubes and 2-8x0.2ml PCR tubes, and two speed options (4,000 & 6,000rpm).
- 3. The electronic braking can reach quick deceleration to reduce handling time.



#### Features

- Compact and cost effective
- Quick release rotor tub, allows for easy rotor exchange
- Two speed options: 4,000 & 6,000rpm
- 2 quick release interchangeable rotors--8x1.5/2.0ml tube rotor, --4 place PCR Strip rotor

Tabspin LA1089

# **Technical Data**

Model	TabSpin006
Capacity	6x1.5/2.0ml, 6x0.5ml tubes and 2-8x0.2ml PCR Strip rotor
Two Speed options	4,000rpm & 6,000rpm
Maximum RCF	1,200 & 2,000 x g
Dimensions	135 x 147 x 120mm (D x W x H)
Weight	0.7kg
Electrical	AC100~240V, 50/60Hz
Dimensions (DxWxH)	270x230x155mm

HiMediaLaboratories<sup>™</sup> www.himedialabs.com

Tel : 00-91-22-6147 1919 / 2500 3747 Email : hdmexpo@himedialabs.com

